

FAQ



LA CROSSE
TECHNOLOGY

WS 7075

✓ What is the maximum distance I can have the remote from the display?

The maximum open-air distance is 25 meters in a straight line although you should take into account distance and resistance. Subtract 6-10 meters for an exterior wall or any obstruction that is similar in width or composition. Subtract 3-10 meters for interior wall or any obstruction that is similar in width or composition. (An obstruction would include anything that is between the line of sight like a roof, walls, floors, ceilings, trees, etc.). Also keep your units away from electronic appliances like TV's, microwaves, computers, refrigerators, and speakers.


✓ Does the remote transmitter have any trouble transmitting through specific materials?


Yes and No. We have trouble maintaining a signal through metal siding, stucco walls, and UV glass. You can get the remote sensor to transmit through these materials, but it will take a little bit of trial and error. Reset the weather station as mentioned above and change the angle that the remote transmits through the siding or glass until an outdoor temperature remains on the display for an extended period of time. Keep in mind that the signal from the remote must travel through some space (10 cm of air minimum) before reaching the metal wall or glass window.

✓ Where can I mount the remote sensor?

In order to get an accurate reading and to prolong the life of your sensor we recommend that you have it in a sheltered area out of the sun and direct rain. Fog and Mist will not affect the sensor, but a soaking in water may.

You can mount it outside under an eave of your house or any other suitable place that will keep it out of the sun and rain. Do not wrap the sensor in plastic or seal it in a plastic bag.





FAQ



LA CROSSE[®]
TECHNOLOGY

✓ How can I get outdoor temperature to show on the display for the first time or after loss of information (i.e. power blackout)?

Bring both units (station + transmitter) inside your house and have the units 1 to 2 meters apart with nothing in-between them.

1. Remove the batteries from both units, display and remote sensor
2. Wait until the display is blank in order to clear all memory (we recommend one minute)
3. Insert the batteries back into the display
4. Taking care NOT to press any buttons, reinstall the batteries into the sensor
5. Do not press any button for at least 10 minutes after installing the batteries. (Let them establish a good connection). Pressing a button during this stage would be enough to stop the search of the sensor which is now being carried out by the station..
6. An outdoor temperature should be showing on your display. You can now put your outdoor sensor back outside.

✓ Why the display of the temperature is different between the outdoor sensor and the station?

You may observe that the station and the remote sensor may show two different temperature values. This is perfectly normal for the sensor collects outdoor temperature data every 60 seconds while the station does every 15 minutes.


✓ How do I reset the MIN/MAX temperatures and humidity?

Press and hold for about 4 seconds the either the IN button to reset the indoor temperatures and humidity values or the OUT button to reset the outdoor temperatures values.

The minimum and maximum values for temperature and humidity that appear then on the screen are the current ones.

✓ What do I do if my display is blank?

Check the polarity on your batteries to make sure they are installed according to the diagrams in the battery compartment. Also make sure that you are using a new good quality alkaline battery. We advised against reloading batteries.



Why is my time incorrect or not displaying at all?

1. The clock of this station receives a signal from Frankfurt (DCF-77) to set the clock to atomic time and the calendar. Sometimes, due to adverse weather or atmospheric conditions you will not be able to receive a signal immediately. The best way to get a signal is to put your clock in a window facing Frankfurt until you see the tower icon appear. If definitely you are not receiving the signal, wait one night during the night time there are less atmospheric disturbances.
2. If your time is off by an increment of 1 hour, 2 hours or more, change your TIME ZONE on zero to have time zone on the atomic time (which is CET meaning Central European Time = Brussels, Paris, Rome, Berlin, Madrid,...). Change time zone on "-1" for Great Britain and Portugal. Match any time zone when receiving DCF-77 signal.
3. For this weather station, the time runs from -9hours up to +9 hours.

How do I manually set my time if I do not wish to use the DCF-77 function? How do I manually set other features of this station?

**** The most recent models of this station have the DCF-77 deactivation function****

If your station is provided with this function, deactivate in the first time the DCF-77 reception function, then proceed as follows :


1. Press and hold the SET button for 5 seconds.
2. The hour will now be flashing: press and release the IN button until correct hour and OUT button until correct minute are displayed. Press then and release the SET button once.
3. The time zone will now be flashing: Press and release the IN button until the correct value (from -9 up to +9 hours) is displayed. Press and release the SET button once.
4. The year will now be flashing: Press and release the IN button until you get the correct year. Press and release the SET button.
5. The month and the day will now be flashing: Press and release the OUT button until the correct month and IN button until the correct day are displayed. Press and release the SET button.
6. The day of the week will now be flashing: Press and release the IN button to select the correct day of the week. Press and release the SET button.

What means when "OFL" instead of data is displayed?

"OFL" is displayed when in- or outdoor temperature or indoor humidity data are "out of range".

NOTA:

- indoor temperature measurement range : from 0 °C to 59.9 °C (* from -9.9 °C to 59.9)
- outdoor temperature measurement range : from -29.9 °C to 69.9 °C (* from -29.9 °C to 69.9 °C)



FAQ



LA CROSSE[®]
TECHNOLOGY

- indoor humidity measurement range : from 19 to 95 % (for stations manufactured between 1999 and 2003) or from 1 to 99 % for stations provided with new Swiss high definition sensor (for stations manufactured in 2004)

In the case of outdoor temperature "OFL" can also be displayed when any interference occurs.

Correct data transmission is usually restored during the next data collection. If that is not the case, you should restart your station (see above).



Weather forecast icons

Weather forecast icon indicates improvement or degradation trend rather than immediate sun or rain as the icon shows.

Example: if current weather is cloudy and the icon of rain is displayed, this does not imply that the station is deficient because it is not raining. It simply means that the atmospheric pressure fell and that weather will be getting poor but not necessarily raining.

Once your station installed, it is recommended to ignore the forecast for the next 24 to 48 hours, in order to leave time to the station and to operate in constant condition and altitude.

Each noticeable and important change of atmospheric pressure will result in a change of icon. In the climates subjected to abrupt weather changes (e.g. sunny to rainy weather) the station will operate more precisely than in a climate with small weather variations (e.g. almost always sunny). In addition, an estimated forecast precision is about 75%.

The **La Crosse Technology** weather stations are the only ones being equipped with a pressure sensor which records pressure variations every 3 hours and which calculates, on a 12 hours average, and displays weather tendency averages. Consequently, the **La Crosse Technology** weather stations are more sensitive and more precise than all other similar products.